

Model SC40E Specification Sheet

Enjoy instant filtered steaming hot drinking water from a stylish dispenser.

SO CONVENIENT...

- Up to 60 cups an hour of steaming hot water, adjustable from 50°C to 98°C.*
- High-clearance swivelling spout enables convenient filling of taller vessels.
- LCD screen indicates your hot water temperature status.
- Filters are so easy to change: automated shut-off valve means you simply unscrew your filter to replace — no need to turn off isolating taps, and no drips!
- Special top-mounted dispenser is easier to install.

* This is the maximum realistic temperature in the tank. The temperature at the tap will be less and will vary. Large drawoffs of hot water will reduce the temperature.

INSTALLATION PRE-REQUIREMENTS

Power Supply

- A standard 10amp 3pin power outlet conveniently placed within 1m of the intended location of the boiler tank. This must be installed by a qualified electrician.

Water Supply

- A standard Cold water supply fitted with a 15mm stop tap situated within easy access of the intended location of the boiler tank. This must be installed by a qualified plumber.
- Supply water pressure must not exceed 10,000kpa with pressure regulator installed.
- Water supply must be microbiologically safe.

Dispenser Mounting

- The top-mounted dispenser is easily installed through a standard 35mm hole.

Drip Tray

- As your Schwan appliance is always full of hot water, we recommend a drained drip tray be used in those applications where any leakage could cause property damage.

Warranty

- Two-year repair or replacement warranty for residential installations. One-year repair or replacement warranty for commercial installations (maximum 6 staff).

Certifications

- Schwan drinking water appliances have been laboratory tested and certified to comply with AS/NZS 60335.1 and AS/NZS 60335.2.15 standards.



SPECIFICATIONS

Model	SC40E	Power Input	1300W
Description	Hot Filtered Drinking Water	Tank Capacity	2.4L
Cups / Hour	60	Inlet Water Pressure:	
Unit Size:		Minimum	240 kpa
Height	302mm	Maximum	700 kpa
Width	200mm	Complies with standards:	
Depth	232mm		AS/NZS 60335.1
Voltage	230V ~50Hz		AS/NZS 60335.2.15

Model SC40E Specification Sheet

